



NOTES:

1. SEE DRAWING 403C FOR FOOTING DIMENSIONS AND REINFORCEMENT TABLE.
2. PIER LOCATION DETERMINED BY ENGINEER.
3. UNDER UNSTABLE CONDITIONS, ENGINEER PLANS FOR PIER DESIGN MUST BE SUBMITTED TO & APPROVED BY THE PUBLIC WORKS DEPARTMENT.
4. PLACE PIERS AT EVERY BELL.
5. ENGINEER TO SUBMIT PIER DESIGN.
6. STEEL REINFORCEMENT TO BE A.S.T.M DESIGNATION A -15 - 54T UNLESS OTHERWISE SPECIFIED, BENDS IN BARS TO CONFORM TO A.C.I. STANDARD.
7. PRECAST PIERS ARE ALLOWED PER PERMISSION OF COUNTY ENGINEER.
8. PROVIDE 1/8 - INCH MINIMUM NEOPRENE PAD BETWEEN PIPE AND CLAMPS.

95% SUBMITTAL

FULTON COUNTY STANDARD DETAIL 403B
CONCRETE PIER AND FOOTING DETAIL
ON ROCK

DATE	REVISIONS	DATE	REVISIONS
M/Y	XXX	M/Y	XXX

DGS/DRN/CHKD: XXX
APPROVED: XXX
DATE: XX-X-XX



FULTON COUNTY PUBLIC WORKS
141 PRYOR ST. ATLANTA, GA. 30303
404-612-7400 FAX: 404-224-0498

DRAWING NO.
403B